





@ansell_lighting






in Ansell Lighting



Z LED PLUS


Z LED PLUS 75W Daylight Microwave Sensor Code: AZLEDPLUS/1/DL/MWS





Warrington: +44 (0) 1942 433333





PRODUCT FEATURES

- Industry leading super high efficiency (200 Im/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- · Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- · Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

| | GENERAL INFORMATION |
|-------------------------------|---------------------|
| Wattage | 75W |
| Lumens Delivered | 15000lm |
| Lm/W | 200lm/W |
| Beam Angle | 110 |
| CRI | 70 |
| ССТ | 6000K |
| Input | 220-240V |
| Operating Temp | -35°C - 50°C |
| SDCM | 4 |
| Product Weight without Packag | ing 2.15 kg |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------------------------|--|
| Light Source | LED | |
| Colour / Finish | Black | |
| IP Rating | IP65 | |
| Class Protection | 1 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Suspended | |
| Lumen Depreciation | L80 100,000h | |
| Warranty (Years) | 6 | |
| CE Mark | Yes | |
| Diameter | 265 mm | |
| Height | 152 mm | |
| Accessories | AZLEDPLUS/REF1, AZLEDPLUS/FB1 | |