



<b>Category</b>	High/Low Bay
<b>Application</b>	Ancillary, Hospitality, Industrial, Retail
<b>Specification</b>	Performance

# Z LED PLUS

Z LED PLUS 75W Cool White  
Code: AZLEDPLUS/1



## PRODUCT FEATURES

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

### GENERAL INFORMATION

<b>Wattage</b>	75W
<b>Lumens Delivered</b>	15000lm
<b>Lm/W</b>	200lm/W
<b>Beam Angle</b>	110
<b>CRI</b>	70
<b>CCT</b>	4000K
<b>Input</b>	220/240V
<b>Operating Temp</b>	-35°C - 50°C
<b>SDCM</b>	4
<b>UGR</b>	30
<b>Product Weight without Packaging</b>	2.15 kg

### TECHNICAL INFORMATION

<b>Light Source</b>	LED
<b>Colour / Finish</b>	Black
<b>IP Rating</b>	IP65
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Lumen Depreciation</b>	L80 100,000h
<b>Warranty (Years)</b>	6
<b>CE Mark</b>	Yes
<b>Diameter</b>	265 mm
<b>Height</b>	152 mm
<b>Accessories</b>	AZLEDPLUS/REF1, AZLEDPLUS/FB1




<b>Category</b>	High/Low Bay
<b>Application</b>	Ancillary, Hospitality, Industrial, Retail
<b>Specification</b>	Performance

# Z LED PLUS

Z LED PLUS 75W Cool White

**Code:** AZLEDPLUS/1



## ACCESSORIES

AZLEDPLUS/REF1	Z LED PLUS 1 & 2 High Bay Aluminium Reflector
AZLEDPLUS/FB1	Z LED PLUS High Bay Mounting Bracket