



Z LED Plus

Part of the High/Low Bay product category



Model Z LED PLUS 75W Cool White
Code AZLEDPLUS/1
Application Ancillary, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	75W
Operating Temp	-35°C - 50°C
Lumens Delivered	15000lm
lm/W	200lm/W
CCT	4000K
UGR	30
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.15 kg
Colour / Finish	Black
Diameter	265 mm
Height	152 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	4
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- High specification IP65 and IK08 ratings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Alternative installation options by means of drop rods, jack chain and catenary wire.

ACCESSORIES

AZLEDPLUS/REF1	Z LED PLUS 1 & 2 High Bay Aluminium Reflector
AZLEDPLUS/FB1	Z LED PLUS High Bay Mounting Bracket



25%*
ENERGY SAVING





Z LED Plus



Part of the High/Low Bay product category

Model Z LED PLUS 75W Cool White
Code AZLEDPLUS/1
Application Ancillary, Hospitality, Industrial, Retail

