











High/Low Bay


Performance




## **Z LED PLUS**

## Z LED PLUS 115W Cool White DALI Emergency Code: AZLEDPLUS/2/DD3/M3








Category

**Application** 

Specification



Ancillary, Hospitality, Industrial, Retail

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings

www.ansell-lighting.com

- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation  $\,$
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

GENERAL INFORMATION			
Wattage	115W		
Lumens Delivered	23000lm		
Lm/W	200lm/W		
Beam Angle	110		
CRI	70		
CCT	4000K		
Input	220-240V		
Operating Temp	0°C - 50°C		
SDCM	4		
UGR	31		
Product Weight without Packaging	2.25 kg		

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	6	
CE Mark	Yes	
Diameter	265 mm	
Height	152 mm	