





# Z LED PLUS

Z LED PLUS 115W Daylight DALI Emergency  
Code: AZLEDPLUS/2/DL/DD3/M3

|                      |  |
|----------------------|--|
| <b>Category</b>      | High/Low Bay                               |
| <b>Application</b>   | Ancillary, Hospitality, Industrial, Retail |
| <b>Specification</b> | Performance                                |



- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation

- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

| GENERAL INFORMATION |            |
|---------------------|------------|
| Wattage             | 115W       |
| Lumens Delivered    | 23000lm    |
| Lm/W                | 200lm/W    |
| Beam Angle          | 110        |
| CRI                 | 70         |
| CCT                 | 4000K      |
| Input               | 220-240V   |
| Operating Temp      | 0°C - 50°C |
| SDCM                | 4          |

| TECHNICAL INFORMATION          |                     |
|--------------------------------|---------------------|
| Light Source                   | LED                 |
| Colour / Finish                | Black               |
| IP Rating                      | IP65                |
| Class Protection               | 1                   |
| Internal / External            | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Suspended  |
| Lumen Depreciation             | L80 100,000h        |
| Warranty (Years)               | 6                   |
| CE Mark                        | Yes                 |
| Diameter                       | 265 mm              |
| Height                         | 152 mm              |

