







Ancillary, Hospitality, Industrial, Retail





High/Low Bay


Performance




## **Z LED PLUS**

## Z LED PLUS 115W Daylight OCTO Smart Control Code: AZLEDPLUS/2/DL/OCTO/M3








Category

**Application** 

Specification



- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- · Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- · Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

GENERAL INFORMATION		
Wattage	115W	
Lumens Delivered	23000lm	
Lm/W	200lm/W	
Beam Angle	110	
CRI	70	
CCT	4000K	
Input	220-240V	
Operating Temp	0°C - 50°C	
SDCM	4	
Product Weight without Packaging	2.26 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	6	
CE Mark	Yes	
Diameter	265 mm	
Height	152 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750