





High/Low Bay

Performance

@ansell_lighting





in Ansell Lighting



ansell_lighting


Ancillary, Hospitality, Industrial, Retail

Z LED PLUS

Z LED PLUS 115W Cool White OCTO Smart Control Code: AZLEDPLUS/2/OCTO








Category

Application

Specification



- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings

www.ansell-lighting.com

- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- · Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- · Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

| GENERAL INFORMATION | | |
|----------------------------------|--------------|--|
| Wattage | 115W | |
| Lumens Delivered | 23000lm | |
| Lm/W | 200lm/W | |
| Beam Angle | 110 | |
| CRI | 70 | |
| CCT | 4000K | |
| Input | 220-240V | |
| Operating Temp | -35°C - 50°C | |
| SDCM | 4 | |
| UGR | 31 | |
| Product Weight without Packaging | 2.15 kg | |
| | | |

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------------------------|--|
| Light Source | LED | |
| Colour / Finish | Black | |
| IP Rating | IP65 | |
| Class Protection | 1 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Suspended | |
| Lumen Depreciation | L80 100,000h | |
| Warranty (Years) | 6 | |
| CE Mark | Yes | |
| Diameter | 265 mm | |
| Height | 152 mm | |
| Accessories | AZLEDPLUS/REF1, AZLEDPLUS/FB1 | |