



Category	High/Low Bay
Application	Ancillary, Hospitality, Industrial, Retail
Specification	Performance

## Z LED PLUS

Z LED PLUS 115W Cool White

Code: AZLEDPLUS/2



### PRODUCT FEATURES

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

### GENERAL INFORMATION

Wattage	115W
Lumens Delivered	23000lm
Lm/W	200lm/W
Beam Angle	110
CRI	70
CCT	4000K
Input	220-240V
Operating Temp	-35°C - 50°C
SDCM	4
UGR	31
Product Weight without Packaging	2.15 kg

### TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Lumen Depreciation	L80 100,000h
Warranty (Years)	6
CE Mark	Yes
Diameter	265 mm
Height	152 mm
Accessories	AZLEDPLUS/REF1, AZLEDPLUS/FB1





Category	High/Low Bay
Application	Ancillary, Hospitality, Industrial, Retail
Specification	Performance

# Z LED PLUS

Z LED PLUS 115W Cool White

Code: AZLEDPLUS/2



## ACCESSORIES

AZLEDPLUS/REF1	Z LED PLUS 1 & 2 High Bay Aluminium Reflector
AZLEDPLUS/FB1	Z LED PLUS High Bay Mounting Bracket