





High/Low Bay

Performance









Z LED PLUS

Z LED PLUS 150W Daylight DALI Code: AZLEDPLUS/3/DL/DD3








Category

Application

Specification



Ancillary, Hospitality, Industrial, Retail

- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings

www.ansell-lighting.com

- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation
- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

GENERAL INFORMATION		
Wattage	150W	
Lumens Delivered	30000lm	
Lm/W	200lm/W	
Beam Angle	110	
CRI	70	
CCT	4000K	
Input	220-240V	
Operating Temp	-35°C - 50°C	
SDCM	4	
Product Weight without Packaging	2.65 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	6	
CE Mark	Yes	
Diameter	300 mm	
Height	162 mm	