# Z LED PLUS

| Category | High/Low Bay |
|---|---|
| Application | Ancillary, Hospitality, Industrial, Retail |
| Specification | Performance |

## Z LED PLUS 150W Daylight OCTO Smart Control
## Code: AZLEDPLUS/3/DL/OCTO



**25%** *
**ENERGY SAVING**





300    162



- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation

- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

| GENERAL INFORMATION | |
|---|---|
| Wattage | 150W |
| Lumens Delivered | 30000lm |
| Lm/W | 200lm/W |
| Beam Angle | 110 |
| CRI | 70 |
| CCT | 6000K |
| Input | 220-240V |
| Operating Temp | -35°C - 50°C |
| SDCM | 4 |
| Product Weight without Packaging | 2.65 kg |

| TECHNICAL INFORMATION | |
|---|---|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Suspended |
| Lumen Depreciation | L80 100,000h |
| Warranty (Years) | 6 |
| CE Mark | Yes |
| Diameter | 300 mm |
| Height | 162 mm |
| Accessories | AZLEDPLUS/REF2, AZLEDPLUS/FB1 |