




# Z LED PLUS

Z LED PLUS 150W Cool White

Code: AZLEDPLUS/3

|               |  |
|---------------|--|
| Category      | High/Low Bay                               |
| Application   | Ancillary, Hospitality, Industrial, Retail |
| Specification | Performance                                |



- Industry leading super high efficiency (200 lm/W minimum) robust LED low/high bay suitable for industrial, commercial and retail applications
- High specification IP65 and IK08 ratings
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Pre-wired with 3M of H05RN-F cable for ease and speed of installation

- Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

## GENERAL INFORMATION

|                                  |              |
|----------------------------------|--------------|
| Wattage                          | 150W         |
| Lumens Delivered                 | 30000lm      |
| Lm/W                             | 200lm/W      |
| Beam Angle                       | 110          |
| CRI                              | 70           |
| CCT                              | 4000K        |
| Input                            | 220-240V     |
| Operating Temp                   | -35°C - 50°C |
| SDCM                             | 4            |
| UGR                              | 33           |
| Product Weight without Packaging | 2.65 kg      |

## TECHNICAL INFORMATION

|                                |                               |
|--------------------------------|-------------------------------|
| Light Source                   | LED                           |
| Colour / Finish                | Black                         |
| IP Rating                      | IP65                          |
| Class Protection               | 1                             |
| Internal / External            | Internal / External           |
| Surface / Recessed / Suspended | Ceiling, Suspended            |
| Lumen Depreciation             | L80 100,000h                  |
| Warranty (Years)               | 6                             |
| CE Mark                        | Yes                           |
| Diameter                       | 300 mm                        |
| Height                         | 162 mm                        |
| Accessories                    | AZLEDPLUS/REF2, AZLEDPLUS/FB1 |

