Z LED Performance Linear

Part of the High/Low Bay product category

7YR IP65 IK10 ON-SITE WARRANTY 2 YEARS

Model	Z LED Performance Linear 2
Code	AZLL2/1
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	150/175/200W
Operating Temp	-30°C - 50°C
Lumens Delivered	24000/28000/32000lm (4000K)
lm/W	160lm/W
CCT	4000/5000/6500K
Beam Angle	120

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	5.222 kg
Colour / Finish	Black
Height	120 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Surface, Suspended
Power Factor	0.9

PRODUCT FEATURES

- Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications
- CCT selectable between 4000K/5000K and 6500K and power selectable between 3 options
- High quality die-cast aluminium construction for optimal thermal performance and increased LED lifespan.
- Plug-and-play Hawk emergency pack enables quick conversion from standard to emergency high bay
- Zhaga 18 Mount for Plug-and-play microwave and PIR sensors (0/1-10V compatable).

ACCESSORIES

AZLL/1/L90	Z LED Performance Linear 90 Open Area Lens
AZLL/1/SMK	Z LED Performance Linear Surface Mount Kit
AHHB/1	Hawk Highbay Emergency Pack





Z LED Performance Linear

Part of the High/Low Bay product category

Model	Z LED Performance Linear 2
Code	AZLL2/1
Application	Industrial













