



# Z LED Performance

Part of the High/Low Bay product category



**Model** Z LED Performance 1 DALI  
**Code** AZLP1/1/DD3  
**Application** Industrial

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	100W
<b>Operating Temp</b>	-20°C to 40°C
<b>Lumens Delivered</b>	18000lm (4000K)
<b>lm/W</b>	180lm/W
<b>CCT</b>	4000/5000/6500
<b>UGR</b>	33
<b>Beam Angle</b>	120

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium, Polycarbonate
<b>Diffuser Material</b>	Polycarbonate
<b>Colour / Finish</b>	Black

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Surface, Suspended
<b>Power Factor</b>	0.9
<b>L70 @ 25°C</b>	L70 54000

## PRODUCT FEATURES

- Robust, high efficacy, LED low/high bay for industrial, commercial and retail applications
- CCT selectable between 4000K, 5000K and 6500K
- Intelligent plug and play emergency pack option offers a quick and simple conversion from standard to emergency highbay
- Plug and play microwave and PIR sensor options, offering maximum energy saving
- Die-cast powder coated construction and heatsink for optimum thermals and performance

## ACCESSORIES

AZLP/MWS	Z LED Performance Plug-in MWS Sensor
AZLP/P	Z LED Performance Sensor Programmer
AZLP/FB1/1	Z LED Performance 1 Mounting Bracket
AZLP1/REF/1	Z LED Performance 1 Aluminium Reflector
AHNB/1	Hawk Highbay Emergency Pack
AHNB/1/DM3	Hawk Highbay Emergency Pack DALI





# Z LED Performance



Part of the High/Low Bay product category

**Model** Z LED Performance 1 DALI  
**Code** AZLP1/1/DD3  
**Application** Industrial

