Z LED Performance

7YR IP65 IK10

Part of the High/Low Bay product category

Model	Z LED Performance 1 OCTO Smart Control
Code	AZLP1/1/OCTO
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	100W
Operating Temp	-20°C to 40°C
Lumens Delivered	18000lm (4000K)
lm/W	180lm/W
CCT	4000/5000/6500
UGR	33
Beam Angle	120

MATERIAL INFORMATION

Main Material	Aluminium, Polycarbonate
Diffuser Material	Polycabonate
Colour / Finish	Black

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface, Suspended
Power Factor	0.9
L70 @ 25°C	L70 54000

PRODUCT FEATURES

- Robust, high efficacy, LED low/high bay for industrial, commercial and retail applications
- CCT selectable between 4000K, 5000K and 6500K
- Intelligent plug and play emergency pack option offers a quick and simple conversion from standard to emergency highbay
- Plug and play microwave and PIR sensor options, offering maximum energy saving
- Die-cast powder coated construction and heatsink for optimum thermals and performance

ACCESSORIES

AZLP/MWS	Z LED Performance Plug-in MWS Sensor
AZLP/P	Z LED Performance Sensor Programmer
AZLP/FB1/1	Z LED Performance 1 Mounting Bracket
AZLP1/REF/1	Z LED Performance 1 Aluminium Reflector
AHHB/1	Hawk Highbay Emergency Pack
AHHB/1/DM3	Hawk Highbay Emergency Pack DALI





Z LED Performance

7YR IP65 IK10

Part of the High/Low Bay product category

Model	Z LED Performance 1 OCTO Smart Control
Code	AZLP1/1/OCTO
Application	Industrial













