



Application	Industrial
Specification	Performance

Z LED Performance

Z LED Performance 2









PRODUCT FEATURES

- Robust, high efficacy, LED low/high bay for industrial, commercial and retail applications
- Intelligent plug and play emergency pack option offers a quick and simple conversion from standard to emergency highbay
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Additional 55° narrow lens option ideal for racking aisles

- CCT selectable between 4000K, 5000K and 6500K
- Plug and play microwave and PIR sensor options, offering maximum energy saving
- · Alternative installation options by means of jack chain and catenary wire
- Bracket accessories available for ceiling or wall mounting

	GENERAL INFORMATION
Wattage	150W
Lumens Delivered	27000lm (4000K)
Lm/W	180lm/W
Beam Angle	120
CRI	80
CCT	4000/5000/6500
Input	220-240V
Operating Temp	-20°C to 40°C
SDCM	3
UGR	33
Product Weight without Packagir	ng 2.661 kg

TECHN	ICAL INFORMATION	
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
IK Rating	IK10	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Surface, Suspended	
Lumen Depreciation	L90 50,000h	
Warranty (Years)	7	
CE Mark	Yes	
Height	320 mm	













Application	Industrial	
Specification	Performance	

Z LED Performance

Z LED Performance 2 **Code**: AZLP2/1





ACCESSORIES		
AZLP/MWS	Z LED Performance Plug-in MWS Sensor	
AZLP/PIR	Z LED Performance Plug-in PIR Sensor	
AZLP/P	Z LED Performance Sensor Programmer	
AZLP2/REF/1	Z LED Performance 2 Aluminium Reflector	
AHHB/1	Hawk Highbay Emergency Pack	
AHHB/1/DM3	Hawk Highbay Emergency Pack DALI	
AZLP/FB2/1	Z LED Performance 2 Mounting Bracket	







Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333