





High/Low Bay

Performance

@ansell\_lighting

Ancillary, Hospitality, Industrial, Retail





in Ansell Lighting




## **Z LED Performance**

Z LED Performance 1 Daylight Code: AZPELED/1/DL








AZPELED/1

Category

**Application** 

Specification



- Robust LED low/high bay for industrial, commercial and retail applications
- Alternative installation options by means of drop rods, jack chain and catenary wire
- · Bracket accessories available for ceiling or wall mounting
- 1-10V dimmable as standard

- · Die-cast powder coated construction and heatsink for optimum thermals and performance
- Additional lens options offer mid (85°) and narrow (55°) beam angles; ideal for racking
- Pre-wired with 1.5M of HO7RN-F cable for ease and speed of installation

GENERAL INFORMATION		
Wattage	100W	
Lumens Delivered	15000lm	
Lm/W	150lm/W	
Beam Angle	110	
CRI	80	
CCT	6500K	
Input	220-240V	
Operating Temp	-30°C - 45°C	
SDCM	3	
UGR	27	
Product Weight without Packaging	2.386 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	308 mm	
Height	181 mm	
Accessories	AZPELED/FB2, AZPELED/REF	