Z LED Linear

Part of the High/Low Bay product category

5YR | IP65 | IK10 | Dimmable | ON-SITE WARRANTY 2 YEARS

Model	Z LED Linear 3 Emergency
Code	AZPLLED/3/M3
Application	Ancillary, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	200W
Operating Temp	0°C - 45°C
Lumens Delivered	28000lm
lm/W	140lm/W
CCT	5000K
Beam Angle	25/115

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	8.07 kg
Colour / Finish	Black
Height	134 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	4
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications
- Surface mounting possible with AZPLLED/LC accessory
- 1.5m Suspension kit supplied as standard
- Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan
- Plug and play microwave sensor option, offering maximum energy saving

ACCESSORIES

AZPLLED/MWS	Z LED Linear Plug-in Microwave Sensor
AZPLLED/LC	Z LED Linear Linking Connector
AZPLLED/MWSP	Z LED Linear Microwave Sensor Programmer





Z LED Linear

Part of the High/Low Bay product category

Model	Z LED Linear 3 Emergency
Code	AZPLLED/3/M3
Application	Ancillary, Hospitality, Industrial, Retail











