



Category	High/Low Bay	
Application	Ancillary, Hospitality, Industrial, Retail	
Specification	Performance	

Z LED Linear

Z LED Linear 3 Emergency Code: AZPLLED/3/M3







PRODUCT FEATURES

- Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications
- 1.5m Suspension kit supplied as standard
- Plug and play microwave sensor option, offering maximum energy saving
- Surface mounting possible with AZPLLED/LC accessory
- Die-cast aluminium construction provides enhanced thermal performance for longer LED
- 0/1-10V dimmable as standard (installer must drill through pilot hole and use an IP rated gland on install)

GENER	RAL INFORMATION
Wattage	200W
Lumens Delivered	28000lm
Lm/W	140lm/W
Beam Angle	25/115
CRI	80
ССТ	5000K
Input	220-240V
Operating Temp	0°C - 45°C
SDCM	4
Product Weight without Packaging	8.07 kg

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP65	
IK Rating	IK10	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	134 mm	
Accessories	AZPLLED/MWS, AZPLLED/LC, AZPLLED/MWSP	
Emergency Output Duration	3 Hr	













Category	High/Low Bay	
Application	Ancillary, Hospitality, Industrial, Retail	
Specification	Performance	

Z LED Linear

Z LED Linear 3 Emergency Code: AZPLLED/3/M3





ACCESSORIES		
AZPLLED/MWS	Z LED Linear Plug-in Microwave Sensor	
AZPLLED/LC	Z LED Linear Linking Connector	
AZPLLED/MWSP	Z LED Linear Microwave Sensor Programmer	



f anselllighting



Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333

