



# Z LED Linear

Part of the High/Low Bay product category



<b>Model</b>	Z LED Linear 3 Emergency
<b>Code</b>	AZPLLED/3/M3
<b>Application</b>	Ancillary, Hospitality, Industrial, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	200W
<b>Operating Temp</b>	0°C - 45°C
<b>Lumens Delivered</b>	28000lm
<b>lm/W</b>	140lm/W
<b>CCT</b>	5000K
<b>Beam Angle</b>	25/115

## MATERIAL INFORMATION

<b>Main Material</b>	Aluminium
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	8.07 kg
<b>Colour / Finish</b>	Black
<b>Height</b>	134 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	1
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	4
<b>CRI</b>	80
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling, Suspended
<b>Power Factor</b>	0.9
<b>L70 @ 25°C</b>	L70 B50 54,000h

## PRODUCT FEATURES

- Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications
- Surface mounting possible with AZPLLED/LC accessory
- 1.5m Suspension kit supplied as standard
- Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan
- Plug and play microwave sensor option, offering maximum energy saving

## ACCESSORIES

AZPLLED/MWS	Z LED Linear Plug-in Microwave Sensor
AZPLLED/LC	Z LED Linear Linking Connector
AZPLLED/MWSP	Z LED Linear Microwave Sensor Programmer





# Z LED Linear

Part of the High/Low Bay product category



**Model** Z LED Linear 3 Emergency  
**Code** AZPLLED/3/M3  
**Application** Ancillary, Hospitality, Industrial, Retail

