D-Cell Dim-to-Warm

Part of the LED Strip product category

Model	D-Cell 24V 9.6W IP65 Dim-to-Warm 5m
Code	D/24/02/65/06/00/S01/01
Application	Hospitality, Residential, Retail

GENERAL INFORMATION

Input	24V
Wattage	9.6W/m
Operating Temp	-20°C - 45°C
Lumens Delivered	960lm/m
LED Strip LEDs Per Metre	224
lm/W	95lm/W
CCT	1800-3000K
Beam Angle	120

MATERIAL INFORMATION

Main Material	Copper,Silicone
Diffuser Material	N/A
Product Weight without Packaging	0.25 kg
Height	5 mm

TECHNICAL INFORMATION

Class Protection	3
Light Source	LED
SDCM (Initial Macadam)	3
CRI	90
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Recessed, Wall
Power Factor	1
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- D-CELL dim to warm LED strip suitable for residential and hospitality applications
- Warm 3000K - 1800K provides great versatility, offering a multi-use solution with one product.
- The 3000K colour temperature can be utilised for task lighting, but when dimmed and changed to 1800K, the output serves to create a more relaxed and intimate light setting
- Fast fit plug and play connections remove the need for time consuming soldering of joints
- Multiple connector packs offer great time saving and ease when working on a large scale project





D-Cell Dim-to-Warm

Part of the LED Strip product category

Model	D-Cell 24V 9.6W IP65 Dim-to-Warm 5m
Code	D/24/02/65/06/00/S01/01
Application	Hospitality, Residential, Retail







