





LED Strip

Performance






Hospitality, Residential, Retail



E-Cell ECO LED Strip

E-Cell 24V 4.8W IP65 White 4000K 5m Code: E/24/01/65/01/40/S01/01





Category

Application

Specification

- Fast fit plug and play connections remove the need for time consuming soldering of joints
- Single colour, RGB and RGBW flexible LED strip with self-adhesive back

· E-CELL eco LED strip suitable for residential and commercial applications

- High LED density (196 LEDs per metre) provides a uniform output reducing spotting and providing a more seamless output of light compared to traditional LED strips
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project
- · Joint and connection accessories sold separately
- 70

GENERAL INFORMATION		
Wattage	4.8W/m	
Lumens Delivered	500lm/m	
Lm/W	105lm/W	
Beam Angle	120	
CRI	90	
CCT	4000K	
Input	24V	
Operating Temp	-20°C - 45°C	
SDCM	3	
Product Weight without Packaging	0.26 kg	

www.ansell-lighting.com

TECHNICAL INFORMATION		
Light Source	LED	
IP Rating	IP65	
Class Protection	3	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Recessed, Wall	
Lumen Depreciation	L70 36,000h	
Warranty (Years)	3	
CE Mark	Yes	
Height	4 mm	
LED Strip LEDs Per Metre	70	

