

E-Cell ECO LED Strip

E-Cell 24V 15W IP65 RGBW 4000K 5m Code: E/24/02/65/04/40/S01/01





- E-CELL eco LED strip suitable for residential and commercial applications
- · Fast fit plug and play connections remove the need for time consuming soldering of joints
- Single colour, RGB and RGBW flexible LED strip with self-adhesive back



| Category | LED Strip | |
|---------------|----------------------------------|--|
| Application | Hospitality, Residential, Retail | |
| Specification | Performance | |

- High LED density (196 LEDs per metre) provides a uniform output reducing spotting and providing a more seamless output of light compared to traditional LED strips
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project
- Joint and connection accessories sold separately
- 60

| GENER | RAL INFORMATION | |
|----------------------------------|-----------------|--|
| Wattage | 15W/m | |
| Lumens Delivered | 315lm/m | |
| Lm/W | 88lm/W | |
| Beam Angle | 120 | |
| CRI | 80 | |
| ССТ | 4000K and RGB | |
| Input | 24V | |
| Operating Temp | -20°C - 45°C | |
| SDCM | 5 | |
| Product Weight without Packaging | 0.26 kg | |
| | | |

| TECHNICAL INFORMATION | | | | |
|--------------------------------|-------------------------|--|--|--|
| Light Source | LED | | | |
| IP Rating | IP65 | | | |
| Class Protection | 3 | | | |
| Internal / External | Internal / External | | | |
| Surface / Recessed / Suspended | Ceiling, Recessed, Wall | | | |
| Lumen Depreciation | L70 36,000h | | | |
| Warranty (Years) | 3 | | | |
| CE Mark | Yes | | | |
| Height | 5 mm | | | |
| LED Strip LEDs Per Metre | 60 | | | |

