

Insell







Hospitality, Residential, Retail

LED Strip

Performance



E-Cell ECO LED Strip

E-Cell 24V 14.4W IP20 White 6500K 10m Code: E/24/04/20/01/65/S02/01





- High LED density (196 LEDs per metre) provides a uniform output reducing spotting and
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project

providing a more seamless output of light compared to traditional LED strips

• Joint and connection accessories sold separately

Category

Application

Specification

- 196
- E-CELL eco LED strip suitable for residential and commercial applications
 Fast fit plug and play connections remove the need for time consuming soldering of joints
 Single colour, RGB and RGBW flexible LED strip with self-adhesive back

GENERAL INFORMATION		
Wattage	14.4W/m	
Lumens Delivered	1580lm/m	
Lm/W	110lm/W	
Beam Angle	120	
CRI	90	
CCT	6500K	
Input	24V	
Operating Temp	-20°C - 45°C	
SDCM	3	
Product Weight without Packaging	0.12 kg	

TECHNICAL INFORMATION			
Light Source	LED		
IP Rating	IP20		
Class Protection	3		
Internal / External	Internal		
Surface / Recessed / Suspended	Ceiling, Recessed, Wall		
Lumen Depreciation	L70 36,000h		
Warranty (Years)	3		
CE Mark	Yes		
Height	2 mm		
LED Strip LEDs Per Metre	196		

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

