





LED Strip

Performance





Hospitality, Residential, Retail



E-Cell ECO LED Strip

E-Cell 24V 14.4W IP65 White 6500K 50m Code: E/24/04/65/01/65/\$05/01





- · E-CELL eco LED strip suitable for residential and commercial applications
- Fast fit plug and play connections remove the need for time consuming soldering of joints
- Single colour, RGB and RGBW flexible LED strip with self-adhesive back
- High LED density (196 LEDs per metre) provides a uniform output reducing spotting and providing a more seamless output of light compared to traditional LED strips
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project
- · Joint and connection accessories sold separately

Category

Application

Specification

• 196

| GENERAL INFORMATION | | |
|----------------------------------|--------------|--|
| Wattage | 14.4W/m | |
| Lumens Delivered | 1440lm/m | |
| Lm/W | 103lm/W | |
| Beam Angle | 120 | |
| CRI | 90 | |
| CCT | 6500K | |
| Input | 24V | |
| Operating Temp | -20°C - 45°C | |
| SDCM | 3 | |
| Product Weight without Packaging | 2.6 kg | |
| | | |

www.ansell-lighting.com

| TECHNICAL INFORMATION | | |
|--------------------------------|-------------------------|--|
| Light Source | LED | |
| IP Rating | IP65 | |
| Class Protection | 3 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Recessed, Wall | |
| Lumen Depreciation | L70 36,000h | |
| Warranty (Years) | 3 | |
| CE Mark | Yes | |
| Height | 4 mm | |
| LED Strip LEDs Per Metre | 196 | |

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750