



Z-Cell Irregular Bend



Part of the LED Strip product category

Model Z-Cell 24V 7.2W IP20 White 3000K 5m
Code Z/24/02/20/01/30/S01/01
Application Hospitality, Residential, Retail

GENERAL INFORMATION

| | |
|--------------------------|--------------|
| Input | 24V |
| Wattage | 7.2W/m |
| Operating Temp | -20°C - 45°C |
| Lumens Delivered | 625lm/m |
| LED Strip LEDs Per Metre | 60 |
| lm/W | 87lm/W |
| CCT | 3000K |
| Beam Angle | 120 |

MATERIAL INFORMATION

| | |
|----------------------------------|---------|
| Main Material | Copper |
| Product Weight without Packaging | 0.05 kg |
| Height | 2 mm |

TECHNICAL INFORMATION

| | |
|------------------------|-----------------|
| Class Protection | 3 |
| Light Source | LED |
| SDCM (Initial Macadam) | 3 |
| CRI | 90 |
| Internal / External | Internal |
| Power Factor | 1 |
| L70 @ 25°C | L70 B50 50,000h |

PRODUCT FEATURES

- Z-CELL irregular bend LED strip suitable for residential, hospitality, retail and commercial applications
- Distinctive PCB design allows strip to bend on the horizontal plane without the need for connectors whilst maintaining continuous light output with no dark spots
- Single colour and RGBW flexible LED strip with self-adhesive back
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project
- Joint and connection accessories sold separately





Z-Cell Irregular Bend



Part of the LED Strip product category

| | |
|--------------------|-------------------------------------|
| Model | Z-Cell 24V 7.2W IP20 White 3000K 5m |
| Code | Z/24/02/20/01/30/S01/01 |
| Application | Hospitality, Residential, Retail |

