



FULL: 100mm  
EYE: 120mm  
GRILL: 130mm

## Aluminium Wall Light

Aluminium white IP65 bulkhead opal diffuser with white grill 18W LED 4200K standard emergency

### DESCRIPTION

Modern and robust design with options including full, eyelid and grid case, black and white finish, and standard, emergency, multi-function microwave and multi-function microwave with emergency.

### FEATURES

- Full circular/eyelid LED array
- Die-cast aluminium base and bezel with polycarbonate diffuser
- Plug in connector between the terminal block and the gear tray. Terminal block is located on the base, allowing for easy wiring and the gear tray to be removed during installation
- Four 20mm cable entries & tamper-proof, captive, stainless steel Allen key screws
- 3 hour maintained mode as standard can be configured for non-maintained operation
- Li-Ion 3.2V 1500mAh battery 5 year warranty - Replacement battery code: EB11

### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	2.9 kg	Energy Efficiency Class	F

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	35,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Die-cast Aluminium base and bezel
Construction Materials Line 2	Polycarbonate diffuser	Dimensions - Height	100 mm
Dimensions - Width	365 mm	Dimensions - Depth	365 mm
IP Rating	IP65		

### PRODUCT INFORMATION

Wattage Combined	18W	CCT Combined	4200K
Luminaire Lumens Combined	1400 lm	lm/W Combined	78 lm/w
Beam Angle	120°	CRI	80





<b>SDCM</b>	<6	<b>Lumen Maintenance</b>	0.7
<b>Emergency Lumen Output</b>	140 lm	<b>Lighting Technology used</b>	LED
<b>Non-Directional or Directional</b>	NDLS	<b>Mains or non-mains</b>	MLS
<b>Connected light source (CLS)</b>	FALSE	<b>Colour tuneable light source</b>	FALSE
<b>High Luminance light source</b>	FALSE	<b>Anti Glare shield</b>	FALSE
<b>Dimmable</b>	Not Dimmable	<b>Correlated Colour temperature type</b>	SINGLE_VALUE
<b>Correlated Colour temperature (K) 1</b>	4,200	<b>CCTI/WATTI: Rated Peak Intensity</b>	520 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
ALEM3BKFUL	Emergency, Black, Full Trim	18	4200 K	1400 lm	78 lm/W
ALEM3WHGRI	Emergency, White, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALMF3BKGR1	Emergency, On / Off Microwave, Black, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALMF3WHEYE	Emergency, Eyelid, White	18	4200 K	1300 lm	72 lm/W
ALMF3WHGRI	Emergency, On / Off Microwave, White, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALMFBKGR1	On / Off Microwave, Black, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALMFWHEYE	On / Off Microwave, Eyelid, White	18	4200 K	1300 lm	72 lm/W
ALMFWHFUL	On / Off Microwave, White, Full Trim	18	4200 K	1400 lm	78 lm/W
ALMFWHGRI	On / Off Microwave, White, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALSTDBKGR1	Standard, Black, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALSTDWHEYE	Standard, Eyelid, White	18	4200 K	1300 lm	72 lm/W
ALSTDWHGRI	Standard, White, Grill Trim	18	4200 K	1400 lm	78 lm/W
ALEM3WHFUL	Emergency, White, Full Trim	18	4200 K	1400 lm	78 lm/W
ALMFBKEYE	On / Off Microwave, Eyelid, Black	18	4200 K	1300 lm	72 lm/W
ALMFBKFUL	On / Off Microwave, Black, Full Trim	18	4200 K	1400 lm	78 lm/W
ALSTDWHFUL	Standard	18	4200 K	1400 lm	78 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB11	Li-ion 3.2V 1500mAh Stick Battery	1 / 1

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	3,297 g
Pallet Layer Qty	12
Pallet Layers	5
Pallet Qty	60
MOM / OPQ	1 / 4

