## **Spec Sheet ALULANT**










## DESCRIPTION

An aesthetically pleasing outdoor lantern with superior construction for domestic and commercial applications. A contemporary update to the more tradition lantern style with in improved energy efficiency utilising the latest LED technology

## **FEATURES**

- · Die-cast Aluminium construction
- · Polycarbonate diffuser



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.75 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Dimensions - Height	235 mm	Dimensions - Width	165 mm
Dimensions - Depth	200 mm		

PRODUCT INFORMATION			
Wattage Combined	8W	CCT Combined	4000K
Luminaire Lumens Combined	570 lm	Im/W Combined	71 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
ALULANT	Standard	8 W	4000 K	570 lm	71 lm/W
ALULANTPIR	PIR	8 W	4000 K	570 lm	71 lm/W

ID//

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	827 g	
Pallet Qty	0	
MOM / OPQ	1/6	







