## **Spec Sheet ALULANTPIR**









## **8W LED Aluminium Lantern**

Aluminium black LED Lantern 8W 3100K IP44 with 110° PIR

## **DESCRIPTION**

An aesthetically pleasing outdoor lantern with superior construction for domestic and commercial applications. A contemporary update to the more tradition lantern style with in improved energy efficiency utilising the latest LED technology with the PIR built into the base

## **FEATURES**

- Die-cast Aluminium construction
- · Polycarbonate diffuser
- 7m detection range
- Time adjustment from 8 seconds to 8 minutes
- Lux level adust from 5 to 1000 lux



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.77 kg
Energy Efficiency Class	F		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Dimensions - Height	255 mm	Dimensions - Width	165 mm
Dimensions - Depth	230 mm		

PRODUCT INFORMATION			
Wattage Combined	8W	CCT Combined	4000K
Luminaire Lumens Combined	570 lm	lm/W Combined	71 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP44		













PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
ALULANT	Standard	8 W	4000 K	570 lm	71 lm/W
ALULANTPIR	PIR	8 W	4000 K	570 lm	71 lm/W



PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	894 g	
Pallet Layer Qty	24	
Pallet Layers	5	
Pallet Qty	120	
MOM / OPQ	1/6	





