



## LED Atom Bulkhead


Wall / ceiling mounted white IP65 rounded rectangular bulkhead opal diffuser 6W LED 4000K

### DESCRIPTION

Highly cost effective, compact, ultra low energy, modern design utility bulkhead

### FEATURES

- Instant start to full illumination level - giving a crisp, super bright light output (4000K)
- Polycarbonate construction: impact and corrosion resistant
- Compact design
- External fixing points: for quick & easy installation
- 3 x 20mm cable entries: offering multiple installation options



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.2 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	25,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	165 mm	Dimensions - Width	115 mm
Dimensions - Depth	75 mm	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	6W	CCT Combined	4000K
Luminaire Lumens Combined	710 lm	lm/W Combined	118 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
Lighting Technology used	LED	Non-Directional or Directional	NDLS



Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,200
Displacement Factor	0.9	CCT1/WATT1: Rated Peak Intensity	221 cd



IP65





IP65

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
ATOM5	Standard	6 W	4000 K	710 lm	118 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	240 g
Pallet Layer Qty	180
Pallet Layers	4
Pallet Qty	720
MOM / OPQ	1 / 20

