Li-Ion Emergency Box

90mm

45mm









5ft 60W 4200K High Output LED Batten with **Emergency**

DESCRIPTION

5ft LED highly efficient traditional style batten fixture, slim profile design with even light distribution, front diffuser and end caps removable to allow for easy wiring at either end of the batten or Besa mounting from the rear of the fitting, available in both standard and high output mode to suit different ceiling heights and task requirements, comes complete with bolt on Emergency downlight attached at the end of the fitting

FEATURES

- · Full photometric data available to enable lighting designs. Light output is equivalent or superior to traditional fluorescent battens.
- · Pressed steel body and polycarbonate diffuser
- LED tray can be removed from the housing for easy installation
- · 20mm knockout glands at each end for through wiring options
- BESA box mounting, gear tray retaining straps & push terminal connections
- Li-Ion 3.2V 1500mAh Battery 1 year warranty Replacement battery code: EB19
- 3 hour non maintained operation
- Built-in battery overcharge protection



TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate	Dimensions - Height	73 mm
Dimensions - Width	1460 mm	Dimensions - Depth	60 mm

PRODUCT INFORMATION			
Wattage Combined	60W	CCT Combined	4000K
Luminaire Lumens Combined	7550 lm	Im/W Combined	126 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
IP Rating	IP20	Emergency Lumen Output	160 lm















PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
BATL4FTEM3	Emergency, 4ft	23 W	4000 K	2950 lm	128 lm/W
BATL5FTEM3	Emergency, 5ft	38 W	4000 K	4750 lm	125 lm/W
BATL5HOEM3	Emergency, 5ft	60 W	4000 K	7550 lm	126 lm/W
BATL6FTEM3	Emergency, 6ft	48 W	4000 K	6050 lm	126 lm/W
BATL6HOEM3	Emergency, 6ft	65 W	4200 K	8400 lm	129 lm/W
BATLED4FT	Non-Dimmable, 4ft	23 W	4000 K	2950 lm	128 lm/W
BATLED5FT	Non-Dimmable, 5ft	38 W	4000 K	4750 lm	125 lm/W
BATLED5HO	Non-Dimmable, 5ft	60 W	4000 K	7500 lm	125 lm/W
BATLED6FT	Non-Dimmable, 6ft	48 W	4000 K	6050 lm	126 lm/W
BATLED6HO	Non-Dimmable, 6ft	65 W	4000 K	8400 lm	129 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
EB2	Ni-Cd 3.6V 2000mAh Stick Battery	1/1

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	1,962 g	
Pallet Layer Qty	24	
Pallet Layers	7	
Pallet Qty	168	
MOM / OPQ	1/0	





