



LED Batten



6ft 65W 4200K High Output LED Batten

DESCRIPTION

6ft LED highly efficient traditional style batten fixture, slim profile design with even light distribution, front diffuser and end caps removable to allow for easy wiring at either end of the batten or Besa mounting from the rear of the fitting, available in both standard and high output mode to suit different ceiling heights and task requirements

FEATURES

- Pressed steel body and polycarbonate diffuser
- LED tray can be removed from the housing for easy installation
- 20mm knockout glands at each end for through wiring options
- BESA box mounting, gear tray retaining straps & push terminal connections



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	1.75 kg

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Steel
Construction Materials Line 2	Polycarbonate	Dimensions - Height	73 mm
Dimensions - Width	1730 mm	Dimensions - Depth	67 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	65W	CCT Combined	4000K
Luminaire Lumens Combined	8400 lm	lm/W Combined	129 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.8
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP20

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	4,000
Chromaticity coordinates x	0.376	Chromaticity coordinates y	0.37
Stroboscopic effect metric (SVM)	0.0	Flicker Metric (pst)	0.0
R9 colour rendering index	17.0	Survival factor @6000hrs	0.9
Claim LED Replace Fluorescent	FALSE	Spectrum report available	Yes
Displacement Factor	0.98	CCT1/WATT1: Rated Peak Intensity	3,314 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BATL4FTEM3	Emergency, 4ft	23	4000 K	2950 lm	128 lm/W
BATL5FTEM3	Emergency, 5ft	38	4000 K	4750 lm	125 lm/W
BATL5HOEM3	Emergency, 5ft	60	4000 K	7550 lm	126 lm/W
BATL6FTEM3	Emergency, 6ft	48	4000 K	6050 lm	126 lm/W
BATL6HOEM3	Emergency, 6ft	65	4200 K	8400 lm	129 lm/W
BATLED4FT	4ft	23	4000 K	2950 lm	128 lm/W
BATLED5FT	5ft	38	4000 K	4750 lm	125 lm/W
BATLED5HO	5ft	60	4000 K	7500 lm	125 lm/W
BATLED6FT	6ft	48	4000 K	6050 lm	126 lm/W
BATLED6HO	6ft	65	4000 K	8400 lm	129 lm/W

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	1,914 g
Pallet Layer Qty	24
Pallet Layers	7
Pallet Qty	168
MOM / OPQ	1 / 6

