



## 10W LED CCT Bulkhead with 120° PIR

Wall mounted black IP65 bulkhead 10W CCT selectable with integral PIR

### DESCRIPTION

Durable and attractive oval waterproof bulkhead with selectable CCT and PIR, perfect for exteriors and high-traffic circulation areas

### FEATURES

- Compact and simple IP65 waterproof bulkhead perfect for exteriors and entryways
- Adjustable CCT to suit installation preferences
- Integral PIR sensor with 120° detection range for useful light when it is needed most
- Adjustable lux level and time adjustment from 10 seconds to 5 minutes to optimise security and efficiency



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.06 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	210 mm	Dimensions - Width	120 mm
Dimensions - Depth	65 mm	IK Rating	IK05
IP Rating	IP65		

### PRODUCT INFORMATION

Wattage Combined	10W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	1166 - 1232 lm	lm/W Combined	117 - 123 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7





Lighting Technology used	LED	Non-Directional or Directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	STEPS	Correlated Colour temperature (K) 1	3,000
Correlated Colour temperature (K) 2	4,000	Correlated Colour temperature (K) 3	6,000
Displacement Factor	0.91	CCT1/WATT1: Rated Peak Intensity	316 cd
CCT2/WATT1: Rated Peak Intensity	346 cd	CCT3/WATT1: Rated Peak Intensity	323 cd





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BHPIRCS	Standard, PIR	10 W	3000 K	1166 lm	117 lm/W
			4000 K	1252 lm	125 lm/W
			6000 K	1232 lm	123 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	128 g
Pallet Layer Qty	120
Pallet Layers	4
Pallet Qty	480
MOM / OPQ	1 / 10

