Spec Sheet BHPIRCS












Wall mounted black IP65 bulkhead 10W CCT selectable with integral PIR

DESCRIPTION

Durable and attractive oval waterproof bulkhead with selectable CCT and PIR, perfect for exteriors and high-traffic circulation areas

FEATURES

- Compact and simple IP65 waterproof bulkhead perfect for exteriors and entryways
- · Adjustable CCT to suit installation preferences
- Integral PIR sensor with 120° detection range for useful light when it is needed most
- Adjustable lux level and time adjustment from 10 seconds to 5 minutes to optimise security and efficiency



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.06 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	210 mm	Dimensions - Width	120 mm
Dimensions - Depth	65 mm		

PRODUCT INFORMATION			
Wattage Combined	10W	CCT Combined	3000К / 4000К / 6000К
Luminaire Lumens Combined	1166 - 1232 lm	lm/W Combined	117 - 123 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP65	IK Rating	IK05













PHOTOMETRICS					
Product Code	Product Type	Watts	ССТ	Luminaire lumens	Lm/W
BHPIRCS		10 W	3000 K	1166 lm	117 lm/W
	Standard, PIR		4000 K	1252 lm	125 lm/W
			6000 K	1232 lm	123 lm/W

IP65	

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	128 g	
Pallet Layer Qty	120	
Pallet Layers	4	
Pallet Qty	480	
MOM / OPQ	1 / 10	









