
Spec Sheet BRICKLED

5 Year Warranty

IP65





Brick Light

LED IP65 stainless steel recessed brick light
4.5W LED 6000K

DESCRIPTION

A modern design that gives an instant cool white light. Ultra low energy consumption and prolonged lamp life.

FEATURES

- Opal diffuser with optional stainless steel frame offering a soft, stylish lighting effect
- Hole cut out size - L: 228mm / D: 75mm / H: 98mm
- Cable gland included
- Integral driver

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Stainless Steel
Application	Internal	**Mounting Type**	Recessed
Product Warranty	5 Years	**Net Weight**	0.54 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	45 °C	**Average Rated Life**	30,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Polycarbonate
Construction Materials Line 2	Stainless steel frame	**Dimensions - Height**	105 mm
Dimensions - Width	233 mm	**Dimensions - Depth**	75 mm
IP Rating	IP65		

PRODUCT INFORMATION			
Wattage Combined	4.5W	**CCT Combined**	6000K
Luminaire Lumens Combined	285 lm	**lm/W Combined**	63 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.7

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet BRICKLED

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	6,000
Chromaticity coordinates x	0.32	**Chromaticity coordinates y**	0.341
Peak Luminous Intensity (cd)	84 cd	**Stroboscopic effect metric (SVM)**	0
Flicker Metric (pst)	0	**R9 colour rendering index**	42
Survival factor @6000hrs	0.9	**Spectrum report available**	Yes
Displacement Factor	0.96	**CCT1/WATT1: Rated Peak Intensity**	84 cd

5 Year Warranty

IP65

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
BRICKLED	Standard	4.5 W	6000 K	285 lm	63 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	668 g
Pallet Layer Qty	96
Pallet Layers	4
Pallet Qty	384
MOM / OPQ	1 / 6