



11W LED Bulkhead


IP65 black wall pack opal diffuser 12W LED 6500K

DESCRIPTION

Robustly constructed traditional style wall pack available in standard or photocell version to enable dusk to dawn setting for additional energy savings. A slightly more compact wall pack giving a lower output compared to the WPACKLED to suit certain walkway and service areas

FEATURES

- Tough polycarbonate housing
- Hinged diffuser
- Opal diffuser
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.92 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	50 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	265 mm	Dimensions - Width	165 mm
Dimensions - Depth	150 mm		

PRODUCT INFORMATION

Wattage Combined	12W	CCT Combined	6500K
Luminaire Lumens Combined	1250 lm	lm/W Combined	104 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
IP Rating	IP65		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BULKLED	Standard	12 W	6500 K	1250 lm	104 lm/W
BULKLEDPC	Photocell	12 W	6500 K	1250 lm	104 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	852 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 12

