
Spec Sheet BULKLED

eterna.

5 Year Warranty

IP65





11W LED Bulkhead

IP65 black wall pack opal diffuser 12W LED 6500K

DESCRIPTION

Robustly constructed traditional style wall pack available in standard or photocell version to enable dusk to dawn setting for additional energy savings. A slightly more compact wall pack giving a lower output compared to the WPACKLED to suit certain walkway and service areas

FEATURES

- Tough polycarbonate housing
- Hinged diffuser
- Opal diffuser
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	Black
Application	External	**Mounting Type**	Surface
Product Warranty	5 Years	**Net Weight**	0.92 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50Hz
Class Protection	1	**Operating Temperature (Min)**	-20 °C
Operating Temperature (Max)	50 °C	**Average Rated Life**	30,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Polycarbonate
Dimensions - Height	265 mm	**Dimensions - Width**	165 mm
Dimensions - Depth	150 mm	**IP Rating**	IP65

PRODUCT INFORMATION			
Wattage Combined	12W	**CCT Combined**	6500K
Luminaire Lumens Combined	1250 lm	**lm/W Combined**	104 lm/w
Beam Angle	120°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.9
Lighting Technology used	LED	**Non-Directional or Directional**	NDLS

CE

UK CA

Member of theLIA

Spec Sheet BULKLED

Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	6,500
Chromaticity coordinates x	0.337	**Chromaticity coordinates y**	0.331
Peak Luminous Intensity (cd)	294 cd	**Stroboscopic effect metric (SVM)**	0.9
Flicker Metric (pst)	1.0	**R9 colour rendering index**	20.0
Survival factor @6000hrs	0.9	**Claim LED Replace Fluorescent**	FALSE
Spectrum report available	Yes	**Displacement Factor**	0.7
CCT1/WATT1: Rated Peak Intensity	294 cd		

5 Year Warranty

IP65

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

5 Year Warranty

IP65

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
BULKLED	Standard	12 W	6500 K	1250 lm	104 lm/W
BULKLEDPC	Photocell	12 W	6500 K	1250 lm	104 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	852 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 12

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D