



IP65



11W LED Bulkhead


IP65 black wall pack opal diffuser 12W LED 6500K with integral photocell

DESCRIPTION

Robustly constructed traditional style wall pack available in standard or photocell version to enable dusk to dawn setting for additional energy savings. A slightly more compact wall pack giving a lower output compared to the WPACKLED to suit certain walkway and service areas

FEATURES

- Tough polycarbonate housing
- Hinged diffuser
- Opal diffuser
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries
- Integral photocell: automatic dusk to dawn operation



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.92 kg
Energy Efficiency Class	D		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	50 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	265 mm	Dimensions - Width	165 mm
Dimensions - Depth	150 mm	IP Rating	IP65

PRODUCT INFORMATION

Wattage Combined	12W	CCT Combined	6500K
Luminaire Lumens Combined	1250 lm	lm/W Combined	104 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
Lighting Technology used	LED	Non-Directional or Directional	NDLS





Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,500
Chromaticity coordinates x	0.307	Chromaticity coordinates y	0.331
Peak Luminous Intensity (cd)	294 cd	Stroboscopic effect metric (SVM)	0.9
Flicker Metric (pst)	1.0	R9 colour rendering index	13.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.7
CCT1/WATT1: Rated Peak Intensity	294 cd		





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BULKLED	Standard	12 W	6500 K	1250 lm	104 lm/W
BULKLEDPC	Photocell	12 W	6500 K	1250 lm	104 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	887 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 12

