



IP65



## 11W LED Bulkhead


IP65 black wall pack opal diffuser 12W LED 6500K with integral photocell

### DESCRIPTION

Robustly constructed traditional style wall pack available in standard or photocell version to enable dusk to dawn setting for additional energy savings. A slightly more compact wall pack giving a lower output compared to the WPACKLED to suit certain walkway and service areas

### FEATURES

- Tough polycarbonate housing
- Hinged diffuser
- Opal diffuser
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries
- Integral photocell: automatic dusk to dawn operation



### GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	External	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.92 kg
Energy Efficiency Class	D		

### TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	50 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	265 mm	Dimensions - Width	165 mm
Dimensions - Depth	150 mm	IP Rating	IP65

### PRODUCT INFORMATION

Wattage Combined	12W	CCT Combined	6500K
Luminaire Lumens Combined	1250 lm	lm/W Combined	104 lm/w
Beam Angle	120°	CRI	80
SDCM	<6	Lumen Maintenance	0.9
Lighting Technology used	LED	Non-Directional or Directional	NDLS





IP65

Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Correlated Colour temperature (K) 1	6,500
Chromaticity coordinates x	0.307	Chromaticity coordinates y	0.331
Peak Luminous Intensity (cd)	294 cd	Stroboscopic effect metric (SVM)	0.9
Flicker Metric (pst)	1.0	R9 colour rendering index	13.0
Survival factor @6000hrs	0.9	Claim LED Replace Fluorescent	FALSE
Spectrum report available	Yes	Displacement Factor	0.7
CCT1/WATT1: Rated Peak Intensity	294 cd		





IP65

## PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
BULKLED	Standard	12	6500 K	1250 lm	104 lm/W
BULKLEDPC	Photocell	12	6500 K	1250 lm	104 lm/W

## PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	887 g
Pallet Layer Qty	60
Pallet Layers	3
Pallet Qty	180
MOM / OPQ	1 / 12

