
Spec Sheet CLEDCIRWH

5 Year Warranty

IP20





CLEDCIRWH

Surface or recessed circular white cabinet downlight 1.7W LED 3000K

DESCRIPTION

Alternative energy efficient option to a traditional halogen lamp ideal for cabinet or kitchen under cabinet lighting, giving a warm white ambient light for functional and subtle lit appearance

FEATURES

- Visually similar to 20W G4 halogen
- 3000K warm colour temperature: offering a pleasing lighting appearance
- Ideal low energy solution to standard halogen cabinet lights
- Not suitable for use with dimmers
- Pre-wired with 2m mains cable and no separate driver required: facilitating easy installation
- 61mm hole cut out size

GENERAL INFORMATION			
Light Source	LED	**Colour / Finish**	White
Application	Internal	**Mounting Type**	Surface, Recessed
Product Warranty	5 Years	**Net Weight**	0.2 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION			
Nominal Voltage	240	**Frequency**	50-60Hz
Class Protection	2	**Operating Temperature (Min)**	-25 °C
Operating Temperature (Max)	40 °C	**Average Rated Life**	30,000 h
Number of switching cycles	15,000	**Construction Materials Line 1**	Zinc Alloy
Construction Materials Line 2	Acrylic	**Dimensions - Height**	70 mm
Dimensions - Width	70 mm	**Dimensions - Depth**	33 mm
IP Rating	IP20		

PRODUCT INFORMATION			
Wattage Combined	1.7W	**CCT Combined**	3000K
Luminaire Lumens Combined	160 lm	**lm/W Combined**	94 lm/w
Beam Angle	100°	**CRI**	80
SDCM	<6	**Lumen Maintenance**	0.8

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk
IE Sales: +353 1 844 6300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37
Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

Spec Sheet CLEDCIRWH

5 Year Warranty

IP20

Lighting Technology used	LED	**Non-Directional or Directional**	NDLS
Mains or non-mains	MLS	**Connected light source (CLS)**	FALSE
Colour tuneable light source	FALSE	**High Luminance light source**	FALSE
Anti Glare shield	FALSE	**Dimmable**	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	**Correlated Colour temperature (K) 1**	3,000
Networked Standby Power	0	**Displacement Factor**	1
CCT1/WATT1: Rated Peak Intensity	50 cd		

5 Year Warranty

IP20

PHOTOMETRICS					
Product Code	**Product Type**	**Watts**	**CCT**	**Luminaire lumens**	**Lm/W**
CLEDCIR	Nickel, Circular	1.7 W	3000 K	160 lm	94 lm/W
CLEDCIRWH	White, Circular	1.7 W	3000 K	160 lm	94 lm/W
CLEDTRI	Nickel, Triangle	1.7 W	3000 K	160 lm	94 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	178 g
Pallet Layer Qty	400
Pallet Layers	5
Pallet Qty	2,000
MOM / OPQ	1 / 40