



CLEDTRI

Surface mounted triangle brushed nickel cabinet downlight 1.7W LED 3000K

DESCRIPTION

Alternative energy efficient option to a traditional halogen lamp ideal for cabinet or kitchen under cabinet lighting, giving a warm white ambient light for functional and subtle lit appearance

FEATURES

- Visually similar to 20W G4 halogen
- 3000K warm colour temperature: offering a pleasing lighting appearance
- Ideal low energy solution to standard halogen cabinet lights
- Not suitable for use with dimmers
- Pre-wired with 2m mains cable and no separate driver required: facilitating easy installation

GENERAL INFORMATION

Light Source	LED	Colour / Finish	Brushed nickel effect
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Net Weight	0.25 kg
Energy Efficiency Class	G		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	2	Operating Temperature (Min)	25 °C
Average Rated Life	30,000 h	Number of switching cycles	15,000
Construction Materials Line 1	Zinc Alloy	Construction Materials Line 2	Acrylic
Dimensions - Height	120 mm	Dimensions - Width	120 mm
Dimensions - Depth	41 mm		

PRODUCT INFORMATION

Wattage Combined	1.7W	CCT Combined	3000K
Luminaire Lumens Combined	160 lm	lm/W Combined	94 lm/w
Beam Angle	90°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		



PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
CLEDCIR	Standard	1.7 W	3000 K	160 lm	94 lm/W
CLEDCIRWH	Standard	1.7 W	3000 K	160 lm	94 lm/W
CLEDTRI	Standard	1.7 W	3000 K	160 lm	94 lm/W

PACKAGING	
Packaging Type	Colour Box
Individual unit gross weight	219 g
Pallet Layer Qty	240
Pallet Layers	4
Pallet Qty	960
MOM / OPQ	1 / 40

