
Spec Sheet COMDL15





eterna.

Year Warranty

IP20

15W Recessed LED Commercial Downlight

Commercial recessed 0-10V dimmable 120mm diameter white downlight 15W LED 4000K 1705lm

DESCRIPTION

The 0-10V dimmable downlight range utilises a highly efficient COB to create a crisp bright environment available in three sizes to meet a range of applications including retail and commercial spaces.

FEATURES

- · Zero maintenance, integral light source providing instant light output
- · LED performance allows for "like for like" replacement of fluorescent PL downlights
- Includes a plug and play constant current 0-10V dimmable LED driver
- · Recessed polished diamond facet reflector with glass front to reduce glare
- Flame retardant aluminium housing, includes spring clips to fix within the ceiling
- Lumen efficacy of up to 113.6 lm / W
- · Ability to be converted into an emergency luminaire
- Hole cut out size: 100mm

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.35 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	Glass	Dimensions - Height	51 mm
Dimensions - Width	120 mm	Dimensions - Depth	120 mm
PRODUCT INFORMATION			
Wattage Combined	15W	CCT Combined	4000K
Luminaire Lumens Combined	1660 lm	Im/W Combined	111 lm/w
Beam Angle	60°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		







Member of 🚺

www.eterna-lighting.co.uk

UK Sales: 01933 673344 | E: sales@eterna-lighting.co.uk IE Sales: +35318446300 | E: sales@eterna-lighting.ie

Registered In England No. 410716 VAT Reg. No. GB 229 3783 37 Registered In Ireland No. 018423 VAT Reg. No. IE 8R73602D

eterna.





		PHOTOMET	TRICS		
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
COMDL15	Standard,100mm	15 W	4000 K	1660 lm	111 lm/W
COMDL25	Standard,164mm	25 W	4000 K	2675 lm	107 lm/W
COMDL40	Standard,224mm	40 W	4000 K	3840 lm	96 lm/W

ACCESSORIES		
Product Code	Description	мом / орд
EBPM3	Emergency Battery Pack	1 / 10
EBPM3LI	Li-Ion Battery Pack	1/40
SEEBPM3	Self-Test Emergency Battery Pack	1 / 10

PACKAGING		
Packaging Type	Plain Box	
Individual unit gross weight	417 g	
Pallet Layer Qty	160	
Pallet Layers	4	
Pallet Qty	640	
MOM / OPQ	1/40	





