
## **Spec Sheet COMDL15**











## 15W Recessed LED **Commercial Downlight**

Commercial recessed 0-10V dimmable 120mm diameter white downlight 15W LED 4000K 1705lm

## DESCRIPTION

The 0-10V dimmable downlight range utilises a highly efficient COB to create a crisp bright environment available in three sizes to meet a range of applications including retail and commercial spaces.

## **FEATURES**

- Zero maintenance, integral light source providing instant light
- · LED performance allows for "like for like" replacement of fluorescent PL downlights
- Includes a plug and play constant current 0-10V dimmable LED
- Recessed polished diamond facet reflector with glass front to reduce glare
- Flame retardant aluminium housing, includes spring clips to fix within the ceiling
- Lumen efficacy of up to 113.6 lm / W
- · Ability to be converted into an emergency luminaire
- Hole cut out size: 100mm

GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.35 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	Glass	Dimensions - Height	51 mm
Dimensions - Width	120 mm	Dimensions - Depth	120 mm

PRODUCT INFORMATION			
Wattage Combined	15W	CCT Combined	4000K
Luminaire Lumens Combined	1660 lm	lm/W Combined	111 lm/w
Beam Angle	60°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP20		
















P20

ACCESSORIES		
Product Code	Description	MOM / OPQ
EBPM3	Emergency Battery Pack	1 / 10
EBPM3LI	Li-Ion Battery Pack	1 / 40
SEEBPM3	Self-Test Emergency Battery Pack	1 / 10

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	417 g
Pallet Layer Qty	160
Pallet Layers	4
Pallet Qty	640
MOM / OPQ	1 / 40







