



**Recessed CT Selectable
Commercial Downlight**
Commercial recessed 0-10V dimmable
170mm diameter white downlight 25W LED
CCT selectable

DESCRIPTION

Dimmable Recessed commercial downlight range including three colour temperature selections available in three sizes. This range is ideal for retrofit commercial applications.

FEATURES

- Zero maintenance, integral light source providing instant light output
- LED performance allows for “like for like” replacement of fluorescent PL downlights
- Includes a plug and play constant current 0-10V dimmable LED driver
- Recessed light source with opal diffuser and polished reflector to reduce glare
- Flame retardant aluminium housing, includes spring clips to fix within the ceiling
- Lumen efficacy of up to 114 lm / W
- Ability to be converted into an emergency luminaire
- Hole cut out size: 150mm

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.81 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Average Rated Life	45,000 h
Number of switching cycles	45,000	Construction Materials Line 1	Die Casting
Construction Materials Line 2	PC	Dimensions - Height	72 mm
Dimensions - Width	170 mm	Dimensions - Depth	170 mm

PRODUCT INFORMATION

Wattage Combined	25W	CCT Combined	3000K / 4000K / 6000K
Luminaire Lumens Combined	2490 - 2580 lm	lm/W Combined	100 - 103 lm/w
Beam Angle	90°	CRI	80
SDCM	<6	Lumen Maintenance	0.7
IP Rating	IP54		





PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
COMRCS25	Standard, 170mm	25 W	3000 K	2490 lm	100 lm/W
			4000 K	2685 lm	107 lm/W
			6000 K	2580 lm	103 lm/W
COMRCS35	Standard, 225mm	35 W	3000 K	3575 lm	102 lm/W
			4000 K	3850 lm	110 lm/W
			6000 K	3690 lm	105 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EBPM3	Emergency Battery Pack	1 / 10
EBPM3LI	Li-Ion Battery Pack	1 / 40
SEEBPM3	Self-Test Emergency Battery Pack	1 / 10

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	902 g
Pallet Qty	0
MOM / OPQ	1 / 20

