
## **Spec Sheet** CR80CR











## **Mains Low Voltage Ceiling Downlight Converter**

Mains or low voltage converter with GU10 and GU5.3 lamp holders polished chrome

## DESCRIPTION

Converts traditional mains R50, R64 and R80 downlight and eyeball dimensions to modern GU10 or low voltage lighting: allows use of modern light source without expensive repairs & decoration

## **FEATURES**

- · Pre-wired with ceramic GU5.3 low voltage lampholder, ceramic GU10 mains lampholder option also included
- Fitting is rated at 50W max
- Converts traditional mains R50, R64 and R80 downlights to GU10 or LV lighting
- Hole cut out 70-140mm replaces a wide range of outdated
- Shallow profile, neat, unobtrusive solution

| GENERAL INFORMATION |                        |                  |          |  |
|---------------------|------------------------|------------------|----------|--|
| Colour / Finish     | Polished chrome effect | Application      | Internal |  |
| Mounting Type       | Recessed               | Product Warranty | 1 Year   |  |
| Net Weight          | 0.3 kg                 |                  |          |  |

| TECHNICAL INFORMATION |        |                               |        |  |
|-----------------------|--------|-------------------------------|--------|--|
| Frequency             | 50Hz   | Construction Materials Line 1 | Steel  |  |
| Dimensions - Height   | 125 mm | Dimensions - Width            | 150 mm |  |
| Dimensions - Depth    | 150 mm |                               |        |  |

| PRODUCT INFORMATION |      |  |
|---------------------|------|--|
| IP Rating           | IP20 |  |













| IP20 |  |
|------|--|

| PACKAGING                       |                 |  |
|---------------------------------|-----------------|--|
| Packaging Type                  | Plastic Blister |  |
| Individual unit gross weight    | 254 g           |  |
| Intermediate Carton Depth (mm)  | 175 mm          |  |
| Intermediate Carton Width (mm)  | 295 mm          |  |
| Intermediate Carton Height (mm) | 175 mm          |  |
| Intermediate Pack Qty.          | 5               |  |
| Pallet Layer Qty                | 200             |  |
| Pallet Layers                   | 3               |  |
| Pallet Qty                      | 600             |  |
| MOM / OPQ                       | 5 / 40          |  |

CE





