Spec Sheet DECKLED










DESCRIPTION

Mains voltage LED compact recessed fixture equally useful for exterior use such as deck lighting, or for interior use recessed into plinths. Complete with colour filters to suit different applications and pre wired with 1 metre rubber cable

FEATURES

- Mains voltage, no separate driver required
- Crisp white light or various colour effects using the included blue, red and green filters
- Pre-wired with 1m rubber cable
- · Complete with mounting sleeve for use in solid surfaces
- Anodized aluminium finish
- · Hole cut out if fitted without sleeve 40mm



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	Matt silver effect
Application	External	Mounting Type	Recessed
Product Warranty	1 Year	Net Weight	0.19 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	55 mm
Dimensions - Width	55 mm	Dimensions - Depth	110 mm

PRODUCT INFORMATION			
Wattage Combined	2W	CCT Combined	4000K
Luminaire Lumens Combined	205 lm	lm/W Combined	103 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.7
IP Rating	IP65		











PHOTOMETRICS					
Product Code	Product Type	Watts	сст	Luminaire lumens	Lm/W
DECKLED	Standard	2 W	4000 K	205 lm	102 lm/W

P65

PACKAGING		
Packaging Type	Colour Box	
Individual unit gross weight	207 g	
Pallet Layer Qty	300	
Pallet Layers	4	
Pallet Qty	1,200	
MOM / OPQ	1/50	







