



2W LED Deck Light


LED deck light 2W LED 4000K IP65 matt silver

DESCRIPTION

Mains voltage LED compact recessed fixture equally useful for exterior use such as deck lighting, or for interior use recessed into plinths. Complete with colour filters to suit different applications and pre wired with 1 metre rubber cable

FEATURES

- Mains voltage, no separate driver required
- Crisp white light or various colour effects using the included blue, red and green filters
- Pre-wired with 1m rubber cable
- Complete with mounting sleeve for use in solid surfaces
- Anodized aluminium finish
- Hole cut out if fitted without sleeve - 40mm



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Matt silver effect
Application	External	Mounting Type	Recessed
Product Warranty	1 Year	Net Weight	0.19 kg
Energy Efficiency Class	E		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	2	Operating Temperature (Min)	-20 °C
Operating Temperature (Max)	45 °C	Average Rated Life	30,000 h
Number of switching cycles	15,000	Construction Materials Line 1	Aluminium
Construction Materials Line 2	PC	Dimensions - Height	55 mm
Dimensions - Width	55 mm	Dimensions - Depth	110 mm
IP Rating	IP65		

PRODUCT INFORMATION

Wattage Combined	2W	CCT Combined	4000K
Luminaire Lumens Combined	205 lm	lm/W Combined	103 lm/w
Beam Angle	120°	CRI	80
SDCM	<4	Lumen Maintenance	0.7





IP65

Lighting Technology used	LED	Non-Directional or Directional	DLS
Mains or non-mains	MLS	Connected light source (CLS)	FALSE
Colour tuneable light source	FALSE	High Luminance light source	FALSE
Anti Glare shield	FALSE	Dimmable	Not Dimmable
Correlated Colour temperature type	SINGLE_VALUE	Chromaticity coordinates x	0.384
Chromaticity coordinates y	0.378	Peak Luminous Intensity (cd)	91.0 cd
Stroboscopic effect metric (SVM)	0.0	Flicker Metric (pst)	0.0
R9 colour rendering index	18.0	Survival factor @6000hrs	0.9
Claim LED Replace Fluorescent	FALSE	Spectrum report available	Yes
Displacement Factor	0.93	CCT1/WATT1: Rated Peak Intensity	91 cd





IP65

PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
DECKLED	Standard	2 W	4000 K	205 lm	103 lm/W

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	207 g
Pallet Layer Qty	300
Pallet Layers	4
Pallet Qty	1,200
MOM / OPQ	1 / 50

