



Recessed Maintained Exit Sign


Recessed LED Maintained Emergency Exit Sign

DESCRIPTION

The 2.5W recessed LED maintained emergency exit sign is designed with a slim low profile construction and provides visibility during both normal operation and emergency conditions. Perfect for commercial and retail applications

FEATURES

- Polycarbonate body with edge lit acrylic blade
- ISO 7010 down arrow fitted as standard with additional up, left and right legends included
- Viewing distance 27m
- Suitable for cut out 330-365mm x 45-75mm for cut out 330-365mm x 45-75mm
- 5 year warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Recessed
Product Warranty	5 Years	Net Weight	0.93 kg

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Construction Materials Line 2	Acrylic	Dimensions - Height	224 mm
Dimensions - Width	380 mm	Dimensions - Depth	90 mm
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	2.5W	CCT Combined	6000K
Luminaire Lumens Combined	50 lm	lm/W Combined	20 lm/w
SDCM	<6	Lumen Maintenance	0.7
Emergency Lumen Output	30 lm	Dimmable	Not Dimmable



