



Recessed Maintained Exit Sign


Recessed LED Maintained Emergency Exit Sign

DESCRIPTION

The 2.5W recessed LED maintained emergency exit sign is designed with a slim low profile construction and provides visibility during both normal operation and emergency conditions. Perfect for commercial and retail applications

FEATURES

- Polycarbonate body with edge lit acrylic blade
- ISO 7010 down arrow fitted as standard with additional up, left and right legends included
- Viewing distance 27m
- Suitable for cut out 330-365mm x 45-75mm
- 5 year warranty



GENERAL INFORMATION

| | | | |
|------------------|----------|-----------------|----------|
| Light Source | LED | Colour / Finish | White |
| Application | Internal | Mounting Type | Recessed |
| Product Warranty | 5 Years | Net Weight | 0.93 kg |

TECHNICAL INFORMATION

| | | | |
|-------------------------------|---------|-------------------------------|---------------|
| Nominal Voltage | 240 | Frequency | 50Hz |
| Class Protection | 1 | Operating Temperature (Min) | 0 °C |
| Operating Temperature (Max) | 45 °C | Average Rated Life | 50,000 h |
| Number of switching cycles | 25,000 | Construction Materials Line 1 | Polycarbonate |
| Construction Materials Line 2 | Acrylic | Dimensions - Height | 224 mm |
| Dimensions - Width | 380 mm | Dimensions - Depth | 90 mm |
| IP Rating | IP20 | | |

PRODUCT INFORMATION

| | | | |
|---------------------------|-------|-------------------|--------------|
| Wattage Combined | 2.5W | CCT Combined | 6000K |
| Luminaire Lumens Combined | 50 lm | lm/W Combined | 20 lm/w |
| SDCM | <6 | Lumen Maintenance | 0.7 |
| Emergency Lumen Output | 30 lm | Dimmable | Not Dimmable |





ACCESSORIES

| Product Code | Description | MOM / OPQ |
|--------------|--------------------------------------|-----------|
| E0IREC | Filler Frame for Replacing LEDMDDEM3 | 1 / 100 |

PACKAGING

| | |
|------------------------------|---------|
| Individual unit gross weight | 1,000 g |
| Pallet Qty | 0 |
| MOM / OPQ | 1 / 6 |

