



Slim Maintained Exitbox


Slim profile Maintained/Non Maintained
Black Exitbox with ISO 7010 legends

DESCRIPTION

A slim emergency exit box with a hinged front for simple installation with a viewing distance of 29m. Perfect for commercial, educational and retail applications

FEATURES

- 3 Hour maintained mode configurable to non maintained
- Wall mounted hinged polycarbonate design
- LED array on base for downward illumination
- ISO 7010 down, up, left and right legends
- 5 year product and battery warranty



GENERAL INFORMATION

Light Source	LED	Colour / Finish	Black
Application	Internal	Mounting Type	Surface
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	0.75 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	45 °C	Average Rated Life	50,000 h
Number of switching cycles	25,000	Construction Materials Line 1	Polycarbonate
Dimensions - Height	187 mm	Dimensions - Width	325 mm
Dimensions - Depth	30 mm	IP Rating	IP20

PRODUCT INFORMATION

Wattage Combined	2W	CCT Combined	6000K
Luminaire Lumens Combined	27 lm	lm/W Combined	14 lm/w
Beam Angle	120°	SDCM	<6
Lumen Maintenance	0.7	Emergency Lumen Output	27 lm
Dimmable	Not Dimmable		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E0ISB1	Emergency	2	6000 K	27 lm	0 lm/W
E0ISW1	White	2	6000 K	27 lm	0 lm/W

ACCESSORIES		
Product Code	Description	MOM / OPQ
E0ISUP	Signs Directive Up Arrow for E0IS	1 / 100
E0ISR	Signs Directive Right Arrow for E0IS	1 / 100
E0ISL	Signs Directive Left Arrow for E0IS	1 / 100
E0ISD	Signs Directive Down Arrow for E0IS	1 / 100

PACKAGING	
Packaging Type	Brown Box
Individual unit gross weight	794 g
Pallet Layer Qty	9
Pallet Layers	6
Pallet Qty	54
MOM / OPQ	1 / 10

