

Vorto


Vorto IP65 Emergency Twin Spot 500lm
6000K

DESCRIPTION

The Vorto IP65 emergency twin spot with 2 adjustable heads giving a combined 500 lumen output for emergency situations. The Vorto is designed for simple and quick installation with a clip on front cover and the use of push fit terminals perfect for commercial, industrial and warehouse applications.

FEATURES

- Polycarbonate IP65 IK08 construction
- Twin 2.5W LED adjustable and tiltable heads
- Quick fit cover and push fit terminals
- 20mm side entry points
- 3 hour non-maintained manual test function
- LiFePO4 3.2V 5500mAh with 5 year warranty



GENERAL INFORMATION			
Light Source	LED	Colour / Finish	White
Application	Internal/External	Mounting Type	Surface, Suspended
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	1 kg		

TECHNICAL INFORMATION			
Nominal Voltage	240 V	Frequency	50-60Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Construction Materials Line 1	Polycarbonate
Dimensions - Height	335 mm	Dimensions - Width	300 mm
Dimensions - Depth	440 mm		

PRODUCT INFORMATION			
Wattage Combined	5W	CCT Combined	6000K
Luminaire Lumens Combined	500 lm	lm/W Combined	100 lm/w
Beam Angle	90°	CRI	70
Lumen Maintenance	0.8	IP Rating	IP65
IK Rating	IK08		





PHOTOMETRICS					
Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
E01VT65EM	Emergency, Non-maintained Emergency, White	5 W	6000 K	500 lm	100 lm/W

ACCESSORIES	
Product Code	Description
EB32	LiFePO4 3.2V 5500mAh Stick Battery

PACKAGING	
Packaging Type	Plain Box
Individual unit gross weight	921 g
Pallet Qty	0
MOM / OPQ	1 / 6

